

# BradPack Accessories-Wash Center Accessories

## BradPack® Wash Center Accessories

### Controls

#### Hand Control with 4" Wristblade Handles

Two 4" wristblade handles provide temperature and volume control plus easy operation. Exposed trim is brass with polished chrome-plated finish. Gooseneck spout satisfies hospital design requirements.

Hand Control with 4" Wristblade Handles



#### Futura Faucet Model 900

Chrome-plated, solid cast brass faucet is actuated when the user's hands enter a broad detection area within the lavatory bowl. Flow automatically stops when hands are removed. Flow rate is .5 GPM.

Futura Model 900



#### 90-75 Metering Faucet

Heavy chrome-plated brass faucet is actuated by light push of button. Provides metering flow of water, for approximately 20 seconds. Unit complies with water and energy conservation requirements. Units can be furnished with Vernatherm mixing valve if desired.

90-75 Metering Faucet



#### Handi-Tap Metering Valve


Valve is actuated by a push button located on front of bowl apron. Provides metered flow of water, adjustable for 5 to 60 seconds. Unit complies with water and energy conservation requirements. Units can be furnished with Vernatherm mixing valve if desired.

Handi-Tap Metering Valve



#### Overflow Drain


Grid with overflow tube assembly provides safety drainage when blockage in bowl occurs. Factory-assembled copper overflow tube is soldered to tailpiece.



### Cabinet

#### Cabinet Lock

For storage compartment security, cabinet lock can be provided. Tumbler lock, keyed like other Bradley equipment, is located below door for convenience.



Document No. 6200

This information is subject to change without formal notice.  
0298RSPML (1 Pages Total)

**Bradley** 

P.O. Box 309, Menomonee Falls, WI 53052-0309  
Phone 1-800-BRADLEY FAX 262-251-5817  
<http://www.bradleycorp.com>  
Technical Information Fax Service: 1-800-BRADFAX