



## Built-in Showers with Concealed Supplies

### Specifications

#### Materials

All exposed materials are stainless steel or chrome-plated brass. Valve bodies are cast brass.

#### Standard Equipment

##### Supply Inlets

Female supply inlets are 1/2".

#### Optional Equipment

##### In-Wall Shower Valve as Selected

For more information on each valve type, please enter the model number in the search box at [www.bradleycorp.com](http://www.bradleycorp.com).

##### Showerhead – 1/2" NPT

Institutional or deluxe type chrome-plated showerhead with bent arm and flange or wall arm.

##### Flow Control

A 1.5 GPM (5.7 LPM) flow control is standard. Actual flow may vary, but will not exceed 2.0 GPM (7.6 LPM) max.

##### Hand Shower

For more information on each hand shower type, please reference the Hand Showers tech data at [www.bradleycorp.com](http://www.bradleycorp.com).

##### Diverter Valve

Lever handle operation for easy transfer of water flow between fixed and hand-held shower. ADA compliant.

##### Tub Spout

Diverter type spout with 1/2" inlet.

##### Showerhead Anchor Plate

3/16" cadmium-plated steel plate furnished with countersunk mounting holes and machine screws provide additional mounting length.

##### Showerhead Back Plate

3/16" cadmium-plated steel plate furnished with couplings, studs and nuts allows most secure anchorage of wall-mounted components.





**Built-in Showers with Concealed Supplies**

Model	Description
<input type="checkbox"/> 1C	Built-In Showers with Concealed Supplies
<b>Optional Selections</b>	
<b>Valve Type (select one):</b>	
<b>Hot/tempered and cold supplies</b>	
<input type="checkbox"/> EF	Equa Flo Pressure Balancing Valve
<input type="checkbox"/> EFT1	Equa Flo Pressure Balancing Valve with Temperature Display
<input type="checkbox"/> C5	Equa-Flo C5 Pressure-Balancing Valve
<input type="checkbox"/> HD	Equa Flo HD Pressure Balancing
<input type="checkbox"/> HDT1	Equa Flo HD Pressure Balancing Valve with Temperature Display
<input type="checkbox"/> TMV	Thermostatic Mixing Valve
<input type="checkbox"/> TMVT1	Thermostatic Mixing Valve with Temperature Display
<input type="checkbox"/> HC	Hot and Cold Compression Valve
<b>Single tempered/cold supply</b>	
<input type="checkbox"/> AST	Air Pushbutton
<input type="checkbox"/> PM	Presto 50B
<input type="checkbox"/> SV	Single Compression Valve
<input type="checkbox"/> SVL	Single Compression Valve w/ Lever
<input type="checkbox"/> TTPA	TouchTime Pushbutton*
<input type="checkbox"/> TTPB	TouchTime Piezo Switch*
<input type="checkbox"/> NONE	No Valve
<b>Supply Stop Type (select one):</b> (included with EF, HD, TMV, EFT1, HDT1, TMVT1 and C5 valves)	
<input type="checkbox"/> ST	Stops in Supply for Valves
<input type="checkbox"/> NONE	No Supply Stops
<b>Showerhead Type (select one):</b>	
<b>Bent Arm and Flange</b>	
<input type="checkbox"/> S115	Standard Showerhead (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> S120	Standard Showerhead (Flow Rate = 2.0 GPM/7.6 LPM)
<input type="checkbox"/> ES1	Economy Soft Flow w/ Ball Joint (Flow Rate = 2.0 GPM/7.6 LPM)
<input type="checkbox"/> D1	Deluxe Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> J1	Multi-Jet Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> LX1	Luxury Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> B1	Axis Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM)
<b>Wall Arm</b>	
<input type="checkbox"/> S15	Standard Showerhead (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> SX15	Severe Service Showerhead (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> S20	Standard Showerhead (Flow Rate = 2.0 GPM/7.6 LPM)
<input type="checkbox"/> SX20	Severe Service Showerhead (Flow Rate = 2.0 GPM/7.6 LPM)
<input type="checkbox"/> SF	Deluxe Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM)
<input type="checkbox"/> ES	Economy Soft Flow w/ Ball Joint (Flow Rate = 2.0 GPM/7.6 LPM)
<input type="checkbox"/> J	Multi-Jet Showerhead w/ Ball Joint (Flow Rate = 1.5GPM/5.7 LPM)
<input type="checkbox"/> LX	Luxury Showerhead w/ Ball Joint (Flow Rate = 1.5GPM/5.7 LPM)
<input type="checkbox"/> B	Axis Showerhead w/ Ball Joint (Flow Rate = 1.5GPM/5.7 LPM)
<input type="checkbox"/> NONE	No Showerhead

<b>Showerhead Options (select one):</b>
<b>Volume Control Type (only available on S15, S20, S115 and S120 showerheads):</b>
<input type="checkbox"/> AKV Allen Key Volume Control
<input type="checkbox"/> LHV Lever Handle Volume Control
<input type="checkbox"/> NONE No Volume Control
<b>Ball Joint Type (only available on S15, S20, S115 and S120 showerheads):</b>
<input type="checkbox"/> LBJ Lockable Ball Joint
<input type="checkbox"/> NONE No Ball Joint
<b>Hand Shower Type** (select one):</b>
<input type="checkbox"/> A24 With 60" flexible hose, 24" ADA Grab Bar and Vacuum Breaker
<input type="checkbox"/> A36 With 60" flexible hose, 36" ADA Grab Bar and Vacuum Breaker
<input type="checkbox"/> B24 With 60" Flexible Hose, 24" Metal Slide Bar and Vacuum Breaker
<input type="checkbox"/> B-30 With 60" flexible hose, 30" Slide Bar
<input type="checkbox"/> E24 With 60" Flexible Hose, 22" Economy Slide Bar and Vacuum Breaker
<input type="checkbox"/> HW With 60" Flexible Hose, Wall Hooks and Vacuum Breaker
<input type="checkbox"/> HS With 60" Flexible Hose, Wall Hooks, Vacuum Breaker and Quick Disconnect
<input type="checkbox"/> SB With 60" Flexible Hose, 24" Metal Slide Bar, Vacuum Breaker and Quick Disconnect
<input type="checkbox"/> SB-30 With 60" flexible hose, 30" Slide Bar and Quick Disconnect
<input type="checkbox"/> NONE No Hand Shower
<b>Diverter Valve Type (select one):</b>
<input type="checkbox"/> DV In-Wall Diverter Valve
<input type="checkbox"/> NONE No Diverter Valve
<b>Tub Spout Type (select one):</b>
<input type="checkbox"/> TS Tub Spout — threaded
<input type="checkbox"/> DJ Tub Spout — slip joint
<input type="checkbox"/> NONE No Tub Spout
<b>Soap Dish Type (select one):</b>
<input type="checkbox"/> SD Wall Mounted Soap Dish
<input type="checkbox"/> RSD Recessed Soap Dish
<input type="checkbox"/> NONE No Soap Dish
<b>Showerhead Anchor Plate Type (select one):</b>
<input type="checkbox"/> AP Anchor Plate for Showerhead***
<input type="checkbox"/> NONE No Anchor Plate for Showerhead
<b>Showerhead Back Plate Type (select one):</b>
<input type="checkbox"/> BP Back Plate for Showerhead***
<input type="checkbox"/> NONE No Back Plate for Showerhead

\*TTPA and TTPB valves require a low-voltage UL/CSA listed 120VAC/12VDC plug-in adapter.

\*\* All Hand Showers are 1.5 GPM (5.7 LPM).

\*\*\* Only available with wall arm showerheads.

Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer.