



- Completely Preassembled Unit
- Ready for Connection to Plumbing Supplies
- No Mounting Frame Required

Specifications

Materials

Ablution panel is 18 gauge type 304 stainless steel. All other exposed parts are stainless steel or chrome-plated brass. Valve bodies are brass casting. Supply inlets are flexible stainless steel hoses.

Standard Equipment

Valve Type

For more information on each valve type, please enter the model number in the search box at www.bradleycorp.com

Wash Spout

Stainless steel Ablution spout or chrome-plated severe service head options with anti-splash 0.5GPM (1.9LPM), 1.0GPM (3.8LPM) or 1.5GPM(5.68LPM) flow.

Hose Supply

Supply is a flexible stainless steel hose option. Inlets are accessible through the back of the panel or through knockouts in the top and bottom covers.

ABL Spout Quick Connect

Plastic tubing to connect valving to spout


Optional Equipment

Grab Bar

For added safety and support for users.

DC International Wall Plug

Low-voltage UL/CSA listed 120V/12VDC plug-in adapter required with TouchTime pushbutton and TouchTime piezo switch.



DC International Wall Plug
261-147A



Required Selections

Valve Type (select one):

- AST** Air Pushbutton
- SV** Single Compression Valve (Default)
- TTPA** TouchTime® Pushbutton*
- TTPB** TouchTime® Piezo Switch*

Supply Stop Type (select one):

- ST** Supply Stops
- NONE** No Supply Stops

Spout Type (select one):

- PSG05** Ablution Spout Satin Finish (Flow Rate=0.5 GPM/1.9 LPM)
- PSG10** Ablution Spout Satin Finish (Flow Rate=1.0 GPM/3.8 LPM)
- HPSG05** Ablution Spout High Polish Finish (Flow Rate=0.5 GPM/1.9 LPM)
- HPSG10** Ablution Spout High Polish Finish (Flow Rate=1.0 GPM/3.8 LPM)
- SXABL** Ablution Severe Service Spout (Flow Rate=1.5 GPM/5.68LPM)
- HHABL** Handheld Ablution Control (Flow Rate=1.0 GPM/3.79LPM)

Quick Connect Kit (select one):

- ABLQC** ABL Spout Quick Connect Kit

Grab Bar Type (select one):

- G18ABL** 18" Security Grab Bar
- G24ABL** 24" Security Grab Bar
- NONE** No Grab Bar

Wall Plug Type (select one):

- DCP** DC International Wall Plug*
- NONE** No Wall Plug

*TTPA and TTPB valves require a low-voltage UL/CSA listed 120VAC/12VDC plug-in adapter.



ABP-1F Individual Flush-Mounted Hand/Foot Washing System

