



Ceiling-Hung Restroom Partitions

Stainless Steel — Series 600

This style is mounted to the ceiling and is recommended where complete floor access is desired. This system requires pre-installed structural ceiling support and is not recommended for ceiling heights over 8'.

Construction

Doors, panels and pilasters consist of two sheet metal faces insulated with a moisture resistant honeycomb core that is adhered to the inner surface and set under pressure to cure. All are manufactured from 300 Series stainless steel with a #4 satin brushed finish.

Permaseal™ Edge

Mills is the only manufacturer to offer the Permaseal Edge. Edges are formed to interlock together to provide a tight fit without crown molding.

Panels

Panels are 1" thick, constructed from 22 gauge stainless steel. Corners are welded underneath a clip that is affixed to all corners.

Doors

Doors are 1" thick, constructed from 22 gauge stainless steel. Corners are welded underneath a clip that is affixed to all corners. Each door includes internal 16 and 14 gauge welded reinforcements at the top and bottom hinge locations with a factory installed concealed true gravity cam. The closing position of each hinge is fully adjustable. A pre-punched hole permits field installation of the ADA-compliant concealed slide latch.

Pilasters

Pilasters are 1 1/4" thick, constructed from 18 gauge stainless steel. The ceiling end of the pilaster shall be provided with an integrally welded 12 gauge leveling bar. Pilasters shall be attached to the ceiling using 3/8"-16 threaded rod(s), hex nuts and washers (included or shipped in advance upon request). Structural support and drilling provided by others.

Hardware

Mills standard hardware is constructed from heavy-duty grade chromed Zamac. Compartments are provided with all hardware and zinc-plated torx-head fasteners to complete installation for applications with masonry block walls.

Door Hardware

Wraparound hinges are thru-bolted to the pilasters and the surface-mounted slide latch includes an emergency egress feature. The slide latch does not require a twisting motion and complies with all Federal ADA guidelines. The strike/keeper is wraparound and thru-bolted. Doors 32" wide or less are provided with a combination coat hook/bumper. Doors 34" wide or 36" wide are provided with an individual coat hook, door bumper and door pulls. Torx-head fasteners are supplied with all hardware.

Brackets

Stirrup-type, single-ear, double-ear and U-brackets are provided with torx-head fasteners.

Shoes

Shoes are 1-piece, 4" high, 304 Series stainless steel with #4 satin brushed finish and are secured to the inside face of the pilaster using stainless steel Torx-head fasteners.



Optional Selections

Finish

- Satin Brushed (STD)

Texture

- 5WL (Requires particle board core pilasters)
- Leather Grain

Door Hardware

- Zamac Surface-Mounted Slide Latch and Keeper
- Stainless Steel Surface-Mounted Slide Latch and Keeper

Hinges

- Chromed Zamac Wraparound Gravity Hinge (STD)
- Stainless Steel Wraparound Gravity Hinge
- Continuous Aluminum Spring-Loaded Hinge
- Continuous Stainless Steel Spring-Loaded Hinge

Brackets

- Chromed Zamac Stirrup Brackets (STD)
- Stainless Steel Stirrup Brackets
- Continuous Stainless Steel Brackets
- Continuous Aluminum Brackets

Miscellaneous

- Grab Bar Reinforcements
- Cutouts
- Solid Particle Board Core (must select for Satin Brushed)
 - Pilasters

Corners

- Clipped Corners (STD)
- Welded Corners/Ground Smooth

Verify all rough-in dimensions prior to installation.

Consult local and national codes. Conformity and compliance to local and national codes is the responsibility of the installer.

Page 1 of 1 9/13/2018

This information is subject to change without notice.

Bradley_Partitions_StainlessSteel_CeilingHung

© 2018 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com